

PRODUCT

Collection	Ascendant: Herringbone and Chevron
Construction	Solid vinyl tile; multi-layer backing system for optimal stability
International Specifications	ASTM F 1700, Class III, Type B – embossed surface
Product Thickness	3mm (0.120 in.)
Edge Type	Herringbone: Micro-beveled edge Chevron: Straight edge
Wear Layer Thickness	20 mil.
Finish	Polyurethane protective coating
Adhesive	Parterre Adhesives: Universal, #539P, Royal Epoxy
Maintenance Options	Polish • No Polish – Spray Buff/No Buff
Warranty	20-Year Commercial Warranty (to view, visit parterreflooring.com > Technical > Warranties)

SIZE AND PACKAGING

Tile Sizes	Herringbone - 4" x 24" x 3mm • 54 pieces/carton • 36 sq. ft./carton • 39.68 lb./carton Chevron - 4.25" x 17" x 3mm • 60 pieces/carton • 30.10 sq. ft./carton • 32.78 lb./carton
Shipping Weight	Contact Customer Service: 888.338.1029 or info@parterreflooring.com

PERFORMANCE

	TEST	REQUIREMENTS	RESULT	
ASTM F 1700	Thickness	ASTM F 386	Nominal ± 0.0005 in.	Meets
	Size	ASTM F 2055	± 0.016 in. per linear foot	Pass
	Squareness	ASTM F 2055	0.010 in. max	Pass
	Residual Indentation	ASTM F 1914	Average < 8%	Pass
	Flexibility	ASTM F 137	≤ 1.0 in., no cracks or breaks	Pass
	Dimensional Stability	ASTM F 2199	0.02017 in. max.	Exceeds per linear foot
	Static Coefficient of Friction/Slip	ASTM D 2047	≥ 0.50	Pass
	Chemical Resistance	ASTM F 925	No more than slight change in surface dulling, attack or stain	Meets or Exceeds
	Resistance to Heat	ASTM F 1514	ΔE ≤ 8	Pass
	Resistance to Light	ASTM F 1515	ΔE ≤ 8	Pass
Supplementary	Static Load Limit	ASTM F 970	No visually apparent indentation	250 psi
	Static Load Limit (Modified)	ASTM F 970 (MOD)	No visually apparent indentation	2,500 psi
	Fire Test Data – Flame Spread	ASTM E 648	0.45 watt/cm ² or more Class I	Meets
	Fire Test Data – Smoke Evolution	ASTM E 662	≤ 450	Meets
	Certified Low Emitting – Material	LEED EQc4.3	-	Meets Guidelines
	Certified Low Emitting – Adhesive	LEED EQc4.1	-	Meets Guidelines
	Indoor Air Quality – Material	FloorScore®	-	Meets Guidelines
	Indoor Air Quality – Adhesives	FloorScore®	-	Meets Guidelines
Indoor Air Quality	CHPS 01350	-	Meets Guidelines	

TECHNICAL INFORMATION

Installation Technical Manual	Visit parterreflooring.com > Technical > Installation > Tile, Plank and Sheet
Maintenance Technical Manual	Visit parterreflooring.com > Technical > Maintenance > General

version 2.3.2021

