

### PRODUCT

Collections	Compete Sports Floor
Construction	Sheet Vinyl Flooring
Product Thickness	2.8 mm (0.110 in.) • 3.5 mm (0.137 in.) • 6 mm (0.236 in.)
Wear Layer Thickness	0.6 mm (0.024 in.)
Finish	Polyurethane protective coating
Adhesive	Parterre Adhesive #539P, #549P, Royal Epoxy
Maintenance Options	Polish • No Polish – Spray Buff/No Buff
Warranty	15-Year Commercial Warranty (to view, visit <a href="http://parterreflooring.com">parterreflooring.com</a> > Technical > Warranties)

### SIZE AND PACKAGING

Roll Size	6 ft. x 49.25 ft. (182 cm x 15 m)* • 32.83 sq. yd.
Roll Weight	2.8 mm - 196 lb. • 3.5 mm - 238 lb. • 6 mm - 400 lb.
Shipping Weight	Contact Customer Service: 888.338.1029 or <a href="mailto:info@parterreflooring.com">info@parterreflooring.com</a>

### PERFORMANCE

		TEST	REQUIREMENTS	RESULT		
				2.8 mm	3.5 mm	6.0 mm
Technical Data	Residual Indentation	ASTM F 1303		0.008 in.	0.018 in.	0.040 in.
	Slip Resistance	ASTM D 1303		0.7	0.7	0.7
	Slip Resistance	ASTM C 1028		0.7	0.7	0.7
	<i>Dry</i>			0.9	0.9	0.9
	<i>Wet</i>					
	Shore Hardness	ASTM D 1415		95-96	90-92	90-92
	Abrasion Resistance	ASTM D 3884		24k cycles	24k cycles	24k cycles
	Static Load @ 250 psi	ASTM F 970		0.001 in.	0.005 in.	0.010 in.
	Static Load @ 750 psi	ASTM F 970		0.001 in.	0.005 in.	0.014 in.
	Static Load @ 2,500 psi	ASTM F 970		0.016 in.	0.019 in.	0.024 in.
	Impact Sound Transmission	ASTM E 492		54	57	59
	Residual Impression	DIN V 18 032-2		0.21mm	0.20mm	0.24mm
	Fire Test Data – Flame Spread	ASTM E 648	0.45 watt/cm <sup>2</sup> or more Class I	Meets	Meets	Meets
	Fire Test Data – Smoke Evolution	ASTM E 662	≤ 450	Meets	Meets	Meets
Sporting Characteristics	Ball Bounce	DIN V 18 032-2		99%	99%	99%
	Ball Rebound	NCAA Rebound Test		Pass	Pass	Pass
	Shock Absorption	DIN V 18 302-2		16%	19%	25%
	Shock Absorption	ASTM F355 (G-max)		850	650	532
	Rolling Load	DIN V 032-2 (@ 10 °C)		21Nm	20Nm	18Nm
	Sliding Properties	DIN B 18 032-2		0.56	0.56	0.57
<i>Minimum</i>			0.60	0.59	0.60	
<i>Maximum</i>						

**TECHNICAL INFORMATION**

---

Installation Technical Manual	Visit <a href="http://parterreflooring.com">parterreflooring.com</a> > Technical > Installation > Compete
Adhesives Technical Manual	Visit <a href="http://parterreflooring.com">parterreflooring.com</a> > Technical > Installation > Adhesives
Maintenance Technical Manual	Visit <a href="http://parterreflooring.com">parterreflooring.com</a> > Technical > Maintenance > General

---

\*Sheet roll width and length of product is a nominal measurement.

*version 9.12.17*