

### PRODUCT

Collection	Rigid Core Click with IXPE Acoustic Backing
Construction	Rigid Core Plank   Limestone + Vinyl
International Specifications	ASTM F 3261, Class III, Type B – embossed surface
Product Thickness	6mm (5mm + 1mm IXPE Acoustic Backing)
Wear Layer Thickness	20 mil
Finish	Polyurethane protective coating
Maintenance Options	Polish • No Polish – Spray Buff/No Buff
Warranty	15-Year Light Commercial Warranty (to view, visit <a href="http://parterreflooring.com">parterreflooring.com</a> > Technical > Warranties)

### SIZE AND PACKAGING

Plank Sizes	7 in. x 47.75 in. • 10 pieces/carton • 23.21 sq. ft./carton • 48 lb./carton
Shipping Weight	Contact Customer Service: 888.338.1029 or <a href="mailto:info@parterreflooring.com">info@parterreflooring.com</a>

### PERFORMANCE

	TEST	REQUIREMENTS	RESULT	
ASTM F 1700	Thickness	ASTM F 387	Nominal ± 0.0005 in.	Pass
	Size	ASTM F 2055	± 0.016 in. per linear foot	Pass
	Squareness	ASTM F 2055	0.010 in. max	Pass
	Residual Indentation	ASTM F 1914	Average < 8%	Pass
	Flexibility	ASTM F 137	≤ 1.0 in., no cracks or breaks	Pass
	Dimensional Stability	ASTM F 2199	0.02017 in. max.	Pass
	Static Coefficient of Friction/Slip	ASTM D 2047	≥ 0.50	Pass
	Chemical Resistance	ASTM F 925	Max. 1 rating in all chemical effects	Pass
	Resistance to Heat	ASTM F 1514	ΔE ≤ 8	Pass
	Resistance to Light	ASTM F 1515	ΔE ≤ 8	Pass
Supplementary	Static Load Limit	ASTM F 970	No visually apparent indentation	Pass
	Certified Low Emitting Product	LEED EQ4.3	-	Meets Guidelines
	Indoor Air Quality	CHPS 01350	-	Meets Guidelines
	Indoor Sound Transmission Test	ASTM E 492	-	IIC: 68 (test condition: 6" concrete slab with drop ceiling)

### TECHNICAL INFORMATION

Installation Technical Manual	Visit <a href="http://parterreflooring.com">parterreflooring.com</a> > Technical > Installation > Tile, Plank and Sheet
Maintenance Technical Manual	Visit <a href="http://parterreflooring.com">parterreflooring.com</a> > Technical > Maintenance > General

version 10.29.2018

