

PRODUCT

Collections	As featured in: Avara Luxury Vinyl Floor & Wall
Construction	Loose Lay Vinyl Plank
International Specifications	ASTM F 1700, Class III, Type B – embossed surface
Product Thickness	5mm (.200 in.)
Wear Layer Thickness	20 mil (0.020 in.)
Finish	Polyurethane protective coating
Adhesive	Perimeter Adhesive required; Parterre Universal Adhesive
Maintenance Options	Polish • No Polish – Spray Buff/No Buff
Warranty	15-Year Commercial Warranty

SIZE AND PACKAGING

Plank Sizes	7.25 in. x 48 in. • 10 pieces/carton • 24.17 sq. ft./carton • 50 lb./carton
Shipping Weight	Contact Customer Service: 888.338.1029 or info@parterreflooring.com

PERFORMANCE

	TEST	REQUIREMENTS	RESULT	
ASTM F 1700	Thickness	ASTM F 386	Nominal \pm 0.0005 in.	Meets
	Size	ASTM F 2055	\pm 0.016 in. per linear foot	Pass
	Squareness	ASTM F 2055	0.010 in. max	Pass
	Residual Indentation	ASTM F 1914	Average < 8%	Pass
	Flexibility	ASTM F 137	\leq 1.0 in., no cracks or breaks	Pass
	Dimensional Stability	ASTM F 2199	0.02017 in. max.	Exceeds per linear foot
	Static Coefficient of Friction/Slip	ASTM D 2047	\geq 0.50	Pass
	Chemical Resistance	ASTM F 925	No more than slight change in surface dulling, attack or stain	Meets or Exceeds
	Resistance to Heat	ASTM F 1514	$\Delta E \leq 8$	Pass
	Resistance to Light	ASTM F 1515	$\Delta E \leq 8$	Pass
Supplementary	Static Load Limit	ASTM F 970	No visually apparent indentation	250 psi
	Static Load Limit (Modified)	ASTM F 970 (MOD)	No visually apparent indentation	2,500 psi
	Fire Test Data – Flame Spread	ASTM E 648	0.45 watt/cm ² or more Class I	Meets
	Fire Test Data – Smoke Evolution	ASTM E 662	\leq 450	Meets
	Certified Low Emitting Product	LEED EQ4.3	-	Meets Guidelines
	Certified Low Emitting Adhesive	LEED EQ4.1	-	Meets Guidelines
	Indoor Air Quality - Adhesives	FloorScore™	-	Meets Guidelines
Indoor Air Quality	CHPS 01350	-	Meets Guidelines	

TECHNICAL INFORMATION

For warranties, installation and maintenance instructions, contact your Parterre Sales Representative or visit our website at: www.parterreflooring.com

version 2.1.19

